

FIDDES FLOOR SEALERS

PREMIER SP SEALER

Fiddes Premier SP Floor Sealer is a high solid, water based 1 component self cross linking floor sealer/primer for the surface treatment of timber floors prior to the application of Fiddes SP Floor Lacquer. Ensure all surfaces are clean, dry and free from any previous finishes. Sand the substrate to 120/150 and remove all traces of dust. Apply evenly and consistently with a roller or good quality brush. Once dry apply the first coat of SP Floor Lacquer. A single coat is recommended following with 2 coats of SP Floor Lacquer. Approximate coverage 8-10 sqm per litre.

Note: High tannin timber surfaces should use Fiddes Barrier Seal in replace of Premier SP Sealer.

Barrier Seal

Barrier Seal produces a quick drying surface barrier coat that is ideal for application onto oily reclaimed or contaminated floor surfaces prior to application of Fiddes Timber Coating Systems. It is ideally used on high resin content timbers and is a quick and efficient start to the perfect finish.

Ensure any previous floor finish has been removed. Sanding may be necessary where contamination is severe. Clean surface with Fiddes Floor Surface Cleaner and allow to dry.

Stir contents thoroughly before and during use and apply in a well ventilated room. Use a good quality bristle or synthetic brush and lay evenly in the direction of the grain where possible.

Drying time: 15 mins Coverage: 14 sqm per litre approx

For all product enquiries and information please contact us today!

10/100 New Street, Ringwood, VIC 3134

Phone: (03) 8813 0338

Email: enquiries@fiddesaustralia.com

www.fiddesaustralia.com

