

# CELLULOSE SEALER

A Pre-catalysed, quick dry, easy-sand sealer, that is ideal for use on hardwood substrates with tighter grain patterns or any timber substrate. Dries to fill the timber grain and once sanded back provides a smooth surface ready for application of chosen topcoats.

## **Preparation**

Sand the wooden substrate in stages, working with a medium sandpaper (120 grit), through to a medium/fine grade (180 -220 grit). Always sand in the direction of the grain pattern where possible, ensuring the removal of any blemishes and glue residue prior to application. Take care to remove all traces of sanding dust and test the chosen sheen level on a similar substrate before application.

Always stir the contents well and ensure to apply in a dust free environment with sufficient ventilation.

## **Application**

Formulated for spray application through conventional, airless or HVLP systems. Also suitable for brush application.

Always stir contents thoroughly.

## **Dry Time**

Touch dry 20 mins. Re-Coat 45 -60 mins.

## **Coverage**

8 sqm per litre approx.

---

**For all product enquiries and information please contact us today!**

13/100 New Street, Ringwood, VIC 3134

Phone: (03) 8813 0338

Email: [enquiries@fiddesaustralia.com](mailto:enquiries@fiddesaustralia.com)

[www.fiddesaustralia.com](http://www.fiddesaustralia.com)

