

# HARD WAX OIL

**A blend of natural oils and waxes offering exceptional durability and resistance for internal timber surfaces including floors, bench tops, furniture and areas subjected to a high degree of wear.**

Produces a quick drying natural matt, silk, satin or gloss water repellent, tread-fast finish that will not peel or flake. Hard Wax Oil is easy to maintain and as a natural replenishable product it is easy to rejuvenate timber when required.

## **Preparation**

Ensure all surfaces are clean, dry and free from previous finish. Minor gaps and holes can be filled with Fiddes Filler Gel if required. Sand the substrate with a fine 120-150 grade sandpaper. Ensure the surface is clean and remove all traces of dust prior to application.

## **Application**

Ensure all areas to be coated are extremely well ventilated during and after application. Always test on a small area prior to initial application. Stir contents thoroughly before and during use. No sealer or primer is required. Maximum 2 coats recommended at a coverage rate of 20-24m<sup>2</sup> per litre depending on density of substrate.

**First Coat** – For floors use a brush or painters pad to cut into the edges first. Apply **THINLY** using a brush or short nap 4-5mm microfibre roller and lay evenly following the direction of the grain. Leave to dry for 4-6 hours in ventilated conditions and if possible good airflow. Longer drying times can be expected with exotic wood species and with unfavourable climate conditions.

**Second Coat** - Check to feel that the first coat feels dry and is not tacky. Using a non-abrasive pad (maroon pad for flooring) lightly abrade the surface. Vacuum/remove dust and apply as per first coat. Leave to dry in well ventilated conditions or preferably overnight. The coating has reached its maximum curing after 7 days. Clean Applicators with White Spirits.

**Maintenance**- We recommend Fiddes after care products to maintain your finish. Fiddes Wood Floor Cleaner and Wood Surface Cleaner are a non-abrasive, rinse free formulation that will ensure the longevity of your timber surface. Do not under any circumstance use bleach, ammonia, or caustic based cleaners.


**\*Spray Application**- Depending on individual spray equipment, Hard Wax Oil can be diluted with Fiddes White Spirits up to a maximum of 10% as required.


## **VISIT OUR YOUTUBE CHANNEL FOR APPLICATION VIDEOS**

For further information go to [www.fiddesaustralia.com](http://www.fiddesaustralia.com)

---

**For all product enquiries and information please contact us today!**  
13/100 New Street, Ringwood, VIC 3134  
Phone: (03) 8813 0338  
Email: [enquiries@fiddesaustralia.com](mailto:enquiries@fiddesaustralia.com)  
[www.fiddesaustralia.com](http://www.fiddesaustralia.com)





## Hard Wax Oil Recommended Accessories



**\*Intended use for Rolling On Fiddes Clear Hard Wax Oil**  
For optimal finish we recommend these accessories to be used for application of our Hard Wax Oil. Further information can be found on our website, Facebook or our [YouTube Channel](#) for Instructional Videos.

**For all product enquiries and information please contact us today!**  
13/100 New Street, Ringwood, VIC 3134  
Phone: (03) 8813 0338  
Email: [enquiries@fiddesaustralia.com](mailto:enquiries@fiddesaustralia.com)  
[www.fiddesaustralia.com](http://www.fiddesaustralia.com)

