

LIMING WAX

Formulated to offer a white shade to stained or bare wood, Fiddes Supreme Liming Wax produces a traditional limed finish associated with period oak furniture. Liming Wax is ideal for application on timbers such as oak, or those that normally exhibit distinctive deep grain pattern. On application, Fiddes Liming Wax fills the open wood pores, offering contrasting white tone and emphasising the grain across the whole surface area, typical of a traditional "Limed" finish.

Preparation

Sand the wooden substrate in stages, working with a medium sandpaper (120 grit), through to a medium/fine grade (180-220). Always sand in the direction of the grain pattern where possible, ensuring the removal of any blemishes and glue residue. To emphasise grain pattern, a clean wire brush can be used to drag along the grain to open pores. Take care to remove all traces of sanding dust prior to application.

Ideal Application

Apply liberally with a lint free cotton cloth or 0000 steel wool, working well into the grain in a circular motion. Once the surface is completely covered, rub lightly across the grain making sure the liming wax remains in the open pores. Leave approximately 5-10 minutes and buff in the direction of the grain with a soft cotton cloth. Finish with a coat of Clear Supreme Wax Polish to further enhance sheen level and protection.

Application

Cloth, Brush, Sponge.

Dry Time

3 Minutes at room temperature.

Coverage

16 sqm per Litre (depending on substrate and method of application).

Coats

1 coat - The application of additional coats will deepen the existing colour/shade and enhance sheen level.

Recommended for use on

Fine Furniture, Doors, Cabinet Work and Panelling

For all product enquiries and information please contact us today!

13/100 New Street, Ringwood, VIC 3134

Phone: (03) 8813 0338

Email: enquiries@fiddesaustralia.com

www.fiddesaustralia.com

