

TINTED HARD WAX OIL

A blend of natural oils and waxes offering exceptional durability and resistance for internal timber surfaces including floors, bench tops, furniture and areas subjected to a high degree of wear.

Produces a quick drying natural matt, silk, satin or gloss water repellent, tread-fast finish that will not peel or flake. Hard Wax Oil is easy to maintain and as a natural replenishable product it is easy to rejuvenate timber when required.

Preparation

Ensure all surfaces are clean, dry and free from previous finish. Minor gaps and holes can be filled with Fiddes Filler Gel if required. Sand the substrate with a fine 120-150 grade sandpaper. Ensure the surface is clean and remove all traces of dust prior to application.

Application

Ensure all areas to be coated are extremely well ventilated during and after application and always test on a small area prior to use. No sealer or primer is required. Stir contents thoroughly before and during use. Maximum 2 coats recommended. Clean applicators with White Spirits.

Floors -

Apply with a brush, trowel or a floor applicator and buff in with a TAN or BEIGE floor pad using a slow speed buffing machine (175 RPM) whilst ragging edges working the product across the floor. Once dry, apply a coat of clear Hard Wax Oil using a short nap microfibre roller. Alternatively, to achieve a similar look without using a buffing machine mix 10% Tinted HWO with clear HWO and roll on using a short nap microfibre roller.

You can also roll the Tinted HWO straight using a short nap microfibre roller being extremely careful not to overlap and to leave roller stop marks.

Furniture -

Brush or roll the Tinted Hard Wax Oil and then using a rag, buff into the surface ensuring the entire surface has been covered. Once dry, apply a coat of clear Hard Wax Oil using a short nap microfibre roller. Alternatively, see above instructions to mix Tinted with Clear Hard Wax Oil.

Additional notes

*When applied using the above methods the Tinted Hard Wax Oil is more of a transparent tint. If the project requires a deeper colour we recommend using a direct stain such as Fiddes Nitro or Light Fast Water Stain before applying a Clear Hard Wax Oil as per instructions.

*Depending on the timber substrate, to achieve a close to raw freshly sanded look, we recommend a coat of White Tinted Hard Wax Oil buffed in, followed by a coat of Clear Hard Wax Oil.

*Always do a test patch first and ensure the substrate is prepared in the same process as the project will be completed.

*Please refer to the Hard Wax Oil Application Sheet for additional application information.

For all product enquiries and information please contact us today!


13/100 New Street, Ringwood, VIC 3134

Phone: (03) 8813 0338

Email: enquiries@fiddesaustralia.com

www.fiddesaustralia.com





Tinted Hard Wax Oil

Recommended Accessories



Beige Pad

Slow Speed Buffing Machine

Fiddes
Floor Oil Brush

Roller Tray

*Intended use for Buffing In Fiddes Tinted HWO

For optimal finish we recommend these accessories to be used for application of our Tinted Hard Wax Oil. Further information can be found on our website, Facebook or our [YouTube Channel](#) for Instructional Videos.

For all product enquiries and information please contact us today!


13/100 New Street, Ringwood, VIC 3134

Phone: (03) 8813 0338

Email: enquiries@fiddesaustralia.com

www.fiddesaustralia.com





Tinted Hard Wax Oil Recommended Accessories



***Intended use for Rolling On Fiddes Tinted Hard Wax Oil**
For optimal finish we recommend these accessories to be used for application of our Hard Wax Oil. Further information can be found on our website, Facebook or our [YouTube Channel](#) for Instructional Videos.

For all product enquiries and information please contact us today!
13/100 New Street, Ringwood, VIC 3134
Phone: (03) 8813 0338
Email: enquiries@fiddesaustralia.com
www.fiddesaustralia.com

