UNIVERSAL DECKING OIL

A water repelling Decking Oil that penetrates deeply into both smooth and planed, rough sawn decking and exterior timber. Formulated to both preserve, protect and restore.

Prevents splitting & surface growth of algae whilst also offering high resistance to wear & water penetration, with excellent beading. Available in a range of Clear and 3 natural colour shades that contain UV filters that resist colour fade.

Ideal for use on all pressure/preservative treated hardwood or softwood Decking, Panelling, Sheds and Fencing.

Slip Rating of R10.

Preparation

Ensure all surfaces are clean, dry and free from any previous finish. Remove any fungal growth, dirt or moss on old timber prior to application. Sand the substrate with an 80 grade sanding paper or 80 grade sanding disk removing all traces of dust.

Application

Apply in dry conditions.

Always test on a small area prior to initial application to check colour shade.

First Coat

Stir contents thoroughly, before and during use.

Apply consistently using a Fiddes Floor brush or 10mm microfibre roller and lay evenly, following the direction of the grain. Leave to dry for 6-12 hours.

Second & Third Coats

Sand lightly if necessary and apply as per first coat.

Longer drying periods may occur during application in cold, damp or humid conditions.

Coverage

A single application will cover approximately 10-20 sqm per litre depending on density of substrate

Re-application

Annual re-application is recommended. In areas of high weather exposure reapplication may be required more frequently.

Tints: Clear, Natural Oak, Chestnut, Harvest Brown

For all product enquiries and information please contact us today!

13/100 New Street, Ringwood, VIC 3134

Phone: (03) 8813 0338

Email: enquiries@fiddesaustralia.com

www.fiddesaustralia.com





www.fiddesaustralia.com

