

# CONCRETE FINISH

Fiddes Concrete Finish is a water based single component self-cross-linking Polyurethane/Acrylic finish for the treatment of concrete surfaces. It is a quick drying, low VOC finish that stabilises internal concrete surfaces, whilst preventing dusting and improving resistance to dirt, oil and stains.

## **Recommended for**

Use on interior concrete screed and floors.

## **Application**

Apply at room temperature. Ensure all areas to be coated are well ventilated during and after application. Always test on a small area prior to initial application. Fiddes Concrete Finish is formulated for application directly and does not require thinning.

## **First Coat**

Stir contents thoroughly before and during use and apply in a well-ventilated room. Apply THINLY and EVENLY using a good quality 10mm microfibre roller or brush. Re-coat in 24hrs. Clean applicator with water.

## **Second Coat**

Apply as first coat.

## **Cleaning & Maintenance**

For regular cleaning, Fiddes Wood Floor Cleaner is recommended.

## **Coverage**

8-10 sqm per litre

## **Notes**

- Allow 21 days before application on new concrete floors.
- Always test intercoat adhesion on a small area prior to major application.
- Do not apply in high temperatures (25c +)
- Longer drying periods may occur during application in cold, damp, or humid conditions.
- Full cure/hardness will be reached in 7 days.
- Store in frost free area.

---

**For all product enquiries and information please contact us today!**

13/100 New Street, Ringwood, VIC 3134

Phone: (03) 8813 0338

Email: [enquiries@fiddesaustralia.com](mailto:enquiries@fiddesaustralia.com)

[www.fiddesaustralia.com](http://www.fiddesaustralia.com)

