

DANISH OIL

Suitable for application on interior and exterior wooden surfaces, Danish Oil penetrates deep into the wood offering a durable natural, water resistant, low sheen finish. Contains Tung Oil, blended with resins and solvents, offering an ideal treatment for Mahogany, Teak and Oak Excellent for wood turning. It does not leave a thick film, peel, chip or crack.

APPLICATION

Ensure all areas to be coated are extremely well ventilated during and after application. Always test on a small area prior to initial application. No primer required. Maximum 3 coats recommended. Apply at room temperature. Fiddes Danish Oil is formulated for application directly, and does not require thinning.

Stir contents thoroughly before and during use, and apply in a warm, well ventilated room. Apply THINLY using a good quality bristle or synthetic brush and lay EVENLY, following the direction of the grain. Remove any surplus material immediately with a cloth, carefully checking all areas for any excess application. Leave to dry 4-6 hours in warm, dry well ventilated conditions, or preferably overnight.

Apply additional coats as per the first. Clean applicator with White Spirit.

Apply 3 coats to new interior timber, and 4 coats to exterior timber.

All soiled cloths should be incinerated after use or washed in warm soapy water and left to dry in open area. Risk of self combustion.

To renovate previous application of Danish Oil, lightly sand area with 150 grit sandpaper, and re-apply.

For regular light maintenance, clean with a damp cloth and wipe dry. Re-application may be necessary where soiling or staining is apparent, following the application details above.

A single application will cover approximately 20-24 square meters per litre, depending on the density of the substrate.

For all product enquiries and information please contact us today!
10/100 New Street, Ringwood, VIC 3134
Phone: (03) 8813 0338
Email: enquiries@fiddesaustralia.com
www.fiddesaustralia.com

