

HARD WAX OIL

A blend of natural oils and waxes offering exceptional durability and resistance for internal timber surfaces including floors, bench tops, furniture and areas subjected to a high degree of wear.

Produces a quick drying natural matt, silk or satin water repellent, tread-fast finish that will not peel or flake. Hard wax oil is easy to maintain and as a natural replenishable product it is easy to rejuvenate timber when required.

Suitable for application onto children's toys – EN 71 – Toy Safety Test

Resistant to liquids: Tested in accordance with BS 3900 G5

Resistant to wear: Tested in accordance with BS 3900 E15

Slip Resistant rating of R11 (Note R12 version available)

Preparation

Ensure all surfaces are clean, dry and free from previous finish. Sand the substrate with a fine 120-150 grade sanding paper removing all traces of dust.

Application

Ensure all areas to be coated are extremely well ventilated during and after application. Always test on a small area prior to initial application. Stir contents thoroughly before and during use. No primer required. Maximum 2 coats recommended.

First Coat – For floors use a brush or painters pad to cut into the edges first. Apply **THINLY** using a brush or short nap/gloss roller and lay evenly following the direction of the grain. Leave to dry for 4-6 hours in ventilated conditions and if possible good airflow.

Second Coat - Check to feel that the first coat feels smooth (this will depend on the type of timber). If the timber feels furry, de-nib the surface by rubbing the coating **LIGHTLY** with a fine sand paper on an applicator, maroon pad or 220 grit screen. Vacuum and apply as first coat. Leave to dry in well ventilated conditions or preferably overnight. The coating has reached its maximum curing after 7 days.

Maintenance- We recommend a Fiddes Floor Reviver Kit to maintain your floor finish. Do not under any circumstance use bleach, ammonia or caustic based cleaners to clean your floor. We recommend using Fiddes Floor Surface Cleaner for regular cleaning requirements.

VISIT OUR YOUTUBE CHANNEL FOR APPLICATION VIDEOS

For further information go to www.fiddesaustralia.com or enquiries@fiddesaustralia.com

For all product enquiries and information please contact us today!

10/100 New Street, Ringwood, VIC 3134

Phone: (03) 8813 0338

Email: enquiries@fiddesaustralia.com

www.fiddesaustralia.com

