

TEAK OIL

Based on special vegetable oils and solvents to give a clear penetrating seal & finish to Teak, Cedar and other bare woods to nourish interior and exterior wood.

Application

Ensure all areas to be coated are extremely well ventilated during and after application. No primer required. Always test on a small area prior to initial application. No primer required. Apply at room temperature. Fiddes Teak Oil is formulated for application directly and does not require thinning.

Stir contents thoroughly before and during use, and apply in a warm, well ventilated room. Apply THINLY using a good quality bristle or synthetic brush and lay EVENLY, following the direction of the grain. Remove any surplus material immediately with a cloth, carefully checking all areas for any excess application. Leave to dry 10-12 hours in warm, dry, well ventilated conditions, or preferably overnight.

Apply additional coats as per the first. Clean applicator with White Spirit.

Coats

Apply 3 coats to new interior timber, and 4 coats to exterior timber.

Re-Application

To renovate previous application of Teak Oil, lightly sand area with 150 grit sandpaper, and re-apply.

Cleaning & Maintenance

For regular light maintenance, clean with a damp cloth and wipe dry. Re-application may be necessary where soiling or staining is apparent, following the application details above.

Coverage

A single application will cover approximately 20-24 square meters per litre, depending on the density of the substrate.

For all product enquiries and information please contact us today!

10/100 New Street, Ringwood, VIC 3134

Phone: (03) 8813 0338

Email: enquiries@fiddesaustralia.com

www.fiddesaustralia.com

