

UNIVERSAL DECKING OIL

A water repelling Decking Oil, that penetrates deeply into both smooth and planed, rough sawn decking and exterior timber.

Formulated to both preserve, protect and restore.

Prevents splitting & surface growth of algae whilst also offering high resistance to wear & water penetration, with excellent beading.

Available in a range of Clear and 3 natural colour shades that contain UV filters that resist colour fade.

Ideal for use on all pressure/preservative treated hardwood or softwood Decking, Panelling, Sheds and Fencing.

Preparation:

- Ensure all surfaces are clean, dry and free from any previous finish.
- Remove any fungal growth, dirt or moss on old timber prior to application.
- Sand the substrate with a medium 120 grit sanding paper, removing all traces of dust.

Application:

- Apply in dry conditions.
- Always test on a small area prior to initial application to check colour shade.

First Coat:

- Stir contents thoroughly, before and during use.
- Apply consistently using a good quality brush or roller and lay evenly, following the direction of the grain.
- Leave to dry for 6-12 hours

Second Coat:

- Sand lightly if necessary and apply as per first coat.
- Longer drying periods may occur during application in cold, damp or humid conditions.

Coverage: A single application will cover approximately 8 sqm per litre depending on density of substrate

For all product enquiries and information please contact us today!

10/100 New Street, Ringwood, VIC 3134

Phone: (03) 8813 0338

Email: enquiries@fiddesaustralia.com

www.fiddesaustralia.com

